

megaSun[®] 7900 Alpha

Technical data

megaSun 7900 alpha	Super Power	Ultra Power	intelliSun
Tubes Canopy	18 x 160 W 2 x 80 W (p2)	18 x 160 W 2 x 80 W (p2)	16 x 160 W 4 x 80 W (p2)
Tubes Side	6 x 160 W	6 x 160 W	4 x 160 W 2 x 80 W (p2)
Tubes Bed	24 x 120 W	24 x 180 W	24 x 180 W
Facial tanner	4 x 280 W (EU) 4 x 280 - 458 W (non EU)	4 x 280 W (EU) 4 x 280 - 458 W (non EU)	4 x 280 W (EU) 4 x 280 - 458 W (non EU)
Shoulder tanner (optional)	2 x 250 W	2 x 250 W	2 x 250 W
Nominal power (with air conditioning)	9.880 W (11.140 W)	10.700 W (11.960 W)	10.700 W (14.060 W)
Air discharge	Exhaust-air socket: Ø 300 mm– 2.095 mm(top) Minimum height of the room 2.400mm		
Minimum capacity (exhaust air)	2.250 m ³ /h	2.250 m ³ /h	2.250 m ³ /h
Fuses	Automatic fuse K-type with safety cut out (3-pole) 3 x 25 A + RCD		
CPI	x	x	standard
electronicPower eP	standard	Sstandard	x
ACS	standard	standard	standard
megaVoice	standard	standard	standard
pureAir	standard	standard	standard
musicVibration	standard	standard	standard
mp3-sound-box + audio-connection	standard	standard	standard
automatic VolumeControl	standard	standard	standard
USB Audio	standard	standard	standard
fourSeasons	standard	standard	standard
evoSystem²	standard	standard	standard
p2-Pigment tube	standard	standard	standard
preSelection	standard	standard	standard
x-traTan	standard	standard	standard
aquaCool	Option	Option	Option
aroma	Option	Option	Option
airCon	Option	Option	Option
easyCare	x	x	Option
central exhaust air socket	Option	Option	Option
Extract air hose	Option	Option	Option
Warm air return circuit	Option	Option	Option
megaTimer	Option	Option	Option

Dimensions (h x w x d): 1.713 mm x 2.380 mm x 1.430 mm (closed)
2.087 mm x 2.380 mm x 1.430 mm (opened)

Weight: ca. 670 kg

The rights to technical and design alterations are reserved.

KBL-Solarien AG · Sunshine Company · Ringstraße 24-26 · 56307 Dernbach · Germany
fon +49(0)2689.9426-0 · fax 9426-66 · eMail megaSun@kbl.de · www.megaSun.de